

FIG. 1

processing system 10



FIG. 2

processing d vice 20



FIG. 3

processing system 20



Transaction Cell - 402

FIG. 4

SRC_AGT_A STATUS	DST_AGT_A STATUS	OVC_1	EOP_ST
SRC_AGT_A STATUS	DST_AGT_A STATUS	OVC_2	EOP_ST
SRC_AGT_A STATUS	DST_AGT_A STATUS	OVC_3	EOP_ST
•	•	•	•
SRC_AGT_A STATUS	DST_AGT_A STATUS	OVC_N	EOP_ST
SRC_AGT_A STATUS	DST_AGT_B STATUS	OVC_1	EOP_ST
SRC_AGT_A STATUS	DST_AGT_B STATUS	OVC_2	EOP_ST
SRC_AGT_A STATUS	DST_AGT_B STATUS	OCV_3	EOP_ST
•	•	•	•
•	•	•	•
•	•	•	•
•	•	•	•
•	•	•	•
•	•	•	•
•	•	•	•
•	•	•	•
•	•	•	•
SRC_AGT_D STATUS	DST_AGT_D STATUS	OVC_N-2	EOP_ST
SRC_AGT_D STATUS	DST_AGT_D STATUS	OVC_N-1	EOP_ST
SRC_AGT_D STATUS	DST_AGT_D STATUS	OVC_N	EOP_ST

Agent Status Information Table - 31

FIG. 5



FIG. 6

Rx MAC modul 60 or 66


data for VC1
generic formatted packet 3
generic formatted packet 2
generic format packet 1
EOP
VC1 segmenting for Tx over physical link
VC1_Z
VC1_Y
VC1_D
VC1_C
VC1_B
VC1_A
mapping into format of physical link
format for physical link
VC1_B
CNTLn
VCn_A
CNTLn-1
VC2_A
CNTL2
VC1_A
CNTL1
mulitiplexed data from a plurlaity of virtual channels
received stream of data
data
segment stream via elastic store
SEG 9
SEG 8
SEG 7
SEG 6
SEG 5
SEG 4
SEG 3
SEG 2
SEG 1
DDS n
DDS n-1
DDSn-2
DDSn-3
DDS 4
DDS 3
DDS 2
DDS 1
decoded data
data
CNTL
data
CNTL
data
CNTL
data
CNTL
routing module coordinates reassembly of packets for each VC
VC1_Z
VC1_Y
packet 3
VC1_D
packet 2
VC1_C
VC1_B
VC1_A
packet 1

6/13

FIG. 7


Source Agent xxx
xxx_SDATA_sw (Data)
Transaction Cell - 402
sw_SGnt_xxx (Grant)
Destination Agent yyy
sw_DData_yyy (Data)
Transaction Cell - 402
sw_DGnt_yyy (Grant)
810
808d
808c
808b
808a
Decision
806
Scheduling Decisions
31
Agent Status Information Table
State Update
802
Switching Module 51
xxx_SReq_sw (Request)
xxx_SReload_sw (Reload)
yyy_DReq_sw (Request)
yyy_DReload_sw (Reload)
yyy_DReset_sw (Reset)

FIG. 8

Switch Interface Signals

Agent	Group	Signal	Description
Source Agent	Request	xxx_sreq_agent_sw[2:0]	Destination agent for which data is available
		xxx_sreq_type_sw	Type of data
		xxx_sreq_vc_sw[4:0]	Destination VC for which data is available
		xxx_sreq_eop_sw	EOP for that data
		xxx_sreq_valid_sw	Previous fields are valid
	Grant	sw_sgnt_agent_xxx[2:0]	Destination agent to which data should be sent
		sw_sgnt_type_xxx	Type of data
		sw_sgnt_vc_xxx[4:0]	Destination VC for which data should be sent
		sw_sgnt_valid_xxx	Previous fields are valid
	Reload	xxx_sreload_eop_sw	EOP of the reloaded destination/VC
		xxx_sreload_valid_sw	There is more data on the destination/VC that just got scheduled
	Data	xxx_sdata_bits_sw[127:0]	Payload (16B)
		xxx_sdata_count_sw[3:0]	Count
		xxx_sdata_tag_sw[27:0]	Tag

FIG. 9

Switch Interface Signals

Agent	Group	Signal	Description
Dest. Agent	Request	yyy_dreq_type_sw	Type of data
		yyy_dreq_vc_sw[4:0]	VC for which space is available
		yyy_dreq_valid_sw	Previous field is valid
	Grant	sw_dgnt_agent_yyy[2:0]	Source agent which will send data
		sw_dgnt_type_yyy	Type of data
		sw_dgnt_vc_yyy[4:0]	VC to which data will be sent
		sw_dgnt_eop_yyy	EOP of the data to be sent
		sw_dgnt_valid_yyy	Previous fields are valid
	Reload	yyy_dreload_valid_sw	There is more space on the VC that just got scheduled
	Data	sw_ddata_bits_yyy[127:0]	Payload (16B)
		sw_ddata_count_yyy[3:0]	Data count
		sw_ddata_tag_yyy[27:0]	Tag
	Reset	Reset yyy_dreset_state_sw	State of the credits after reset

FIG. 10


Non Response Input/
Output Transaction
1102
1104
Control
1106
Data
1108
Data
Tag
(CMD=1)
1110
Data
Tag
(CMD=0)
1112
Data
Tag
(CMD=0)
1114
Data
Tag
(CMD=0)
Transaction cell 1
Transaction cell 2
Transaction cell 3
Transaction cell 4

FIG. 11


Response Input/Output
Transaction
1202
1204
Control
1206
Data
1208
Data
Tag
(CMD=1)
1210
Data
Tag
(CMD=0)
1212
Data
Tag
(CMD=0)
Transaction cell 1
Transaction cell 2
Transaction cell 3

FIG. 12


Packet Data Transaction
1252
1254
Control
1256
Data
1258
1260
1262
1264
Data
Tag (CMD=1)
Transaction cell 1
Transaction cell 2
Transaction cell 3
Transaction cell N

FIG. 13


start
1302
source agent places request to switching module indicating that it has one beat worth of data available to transfer
1304
destination agent places a request to indicate to the switch that it has one space available for a particular output virtual channel
1306
switch scheduler waits
1308
schedule transaction cell transfer
1310
one or both scheduled agents requests reload (for same transfer parameters)
1312
wait for several data beat cycles
1314
switch sets multiplexer to service source agent and destination agent
1316
source agent transfers transaction cell to destination agent
end

FIG. 14